7E-A
Portable Phlegm Suction Unit
CE & CFDA APPROVED

Technical data:
Input power: 90VA
Max negative pressure value: ⩾0.075MPa
Pumping rate: ⩾17L/min
Operation noise: ⩽ 65dB (A)
Reservoir volume: 1000mL, 1piece
Working system: short running

YX301
Pulse Oximeter
CE & CFDA APPROVED

0.96" OLED screen
SPO2 and Pulse rate
Gravity sensor
Low-power alarm
Four directions display
Photoplethysmography
Clinical Services and In-home Assistance
Performance in favorable in various environments

YT-1
Infrared Forehead Thermometer
CE & CFDA APPROVED

• Measurement range :	Human body temperature mode: 32.0℃~43.0℃
• Display Resolution :	0.1℃
• Measurement place :	Forehead
• Accuracy :	32.0℃~34.9℃, maximum permissible error ±0.3℃
	35.0℃~42.0℃, maximum permissible error ±0.2℃
	42.1℃~42.9℃, maximum permissible error ±0.3℃
• Display screen :	LCD screen with 4-digit and special icons
• Operating environment :	10℃~40℃
• Max. relative humidity :	≤85%
• Storage environment :	-20℃~+55℃
• Max. relative humidity :	≤85%
• Battery:	2×1.5V AAA batteries

8F-5AW
Oxygen Concentrator
CE & CFDA APPROVED

Global sales leader

Medical grade

95.5%−87% oxygen concentration

5L oxygen flow

Flow Range: 0.5 ~ 5L/min
Oxygen Concentration: 95.5%−87%
Maximum Outlet Pressure: 40 ~ 70kPa
Sound Level: Front side 48dB(A)(average), Whole unit 52dB(A)
Input Power: 400VA
Weight: 15.5kg (34.1 lbs)
Dimension: H50cm(19.7″) × W39cm(15.4″) × D 24.5cm(9.6″)
Minimum Operating Time: 30minutes

YF-02

Noise:< 26 dBa
Vented mask
pressure range from 4-30 cmH2O

YF-01

Noise:< 26 dBa
Vented mask
pressure range from 4-30 cmH2O

YH730
Bi-Level
CE & CFDA APPROVED

Specification	BreathCare PAP				
Product Number	YH-360	YH-560/580	YH-720	YH-725	YH-730
Mode	CPAP	CPAP、Auto CPAP	CPAP、S、T、ST、VGPS	CPAP、S、T、ST、VGPS	CPAP、S、T、ST、VGPS
Pressure	4-20cmH₂O	4-20cmH₂O	4-20cmH₂O	4-25cmH₂O	4-30cmH₂O
Efficient humidifier	●	●	●	●	●
Smart Start/Stop	●	●	×	×	×
FPS-Tech	●	●	×	×	×
High Pressure Reminder	×	×	●	●	●
Leak Reminder	●	●	●	●	●
Asphyxiation Reminder	×	×	●	●	●
Trigger Adjustment	×	×	●	●	●
Cycle Adjustment	×	×	●	●	●
Slope Adjustment	×	×	●	●	●
Tidal Volume Adjustment	×	×	●	●	●
Altitude Adjustment	●	●	●	●	●
Leak Compensation	●	●	●	●	●
Data Management	●	●	●	●	●

YH830
Bi-Level
CE & CFDA APPROVED

Specification	BreathCare PAP II				
Product Number	YH-450	YH-480	YH-820	YH-825	YH-830
Mode	CPAP	CPAP、Auto CPAP	CPAP、S、T、ST、VGPS	CPAP、S、T、ST、VGPS	CPAP、S、T、ST、VGPS
Pressure	4-20cmH_2O	4-20cmH_2O	4-20cmH_2O	4-25cmH_2O	4-30cmH_2O
Efficient humidifier	●	●	●	●	●
Smart Start/Stop	●	●	×	×	×
FPS-Tech	●	●	×	×	×
High Pressure Reminder	×	×	●	●	●
Leak Reminder	●	●	●	●	●
Asphyxiation Reminder	×	×	●	●	●
Trigger Adjustment	×	×	●	●	●
Cycle Adjustment	×	×	●	●	●
Slope Adjustment	×	×	●	●	●
Tidal Volume Adjustment	×	×	●	●	●
Altitude Adjustment	●	●	●	●	●
Leak Compensation	●	●	●	●	●
Data Management	●	●	●	●	●
Central Apnea Detection	●	●	×	×	×
Smart Humidification	●	●	●	●	●

YH830
Mobile Bi-Level （For Hospital)
CE & CFDA APPROVED

Vertical body improves interactive experience.

New UI interactive interface design, more user friendly.

The user-friendly controls, intuitive interface and color LCD screen make it simple to navigate menus and customize comfort settings.

Integration humidification tank design, easy and elegant.